

| Referans Nr. | dx         | a    | e  | k  | h-H    | e1 | e2 | c  | s  | f  | sw |      |
|--------------|------------|------|----|----|--------|----|----|----|----|----|----|------|
| 1630-2022200 | M20x22x200 | 21.7 | 35 | 14 | 25-75  | 49 | 69 | 92 | 12 | 30 | 30 | 1635 |
| 1630-2022250 | M20x22x250 | 21.7 | 35 | 14 | 70-120 | 49 | 69 | 92 | 12 | 30 | 30 | 1720 |
| 1630-2424200 | M24x24x200 | 23.7 | 40 | 16 | 25-75  | 53 | 74 | 92 | 12 | 30 | 36 | 2075 |
| 1630-2424250 | M24x24x250 | 23.7 | 40 | 16 | 70-120 | 53 | 74 | 92 | 12 | 30 | 36 | 2250 |
| 1630-2428200 | M24x28x200 | 27.7 | 44 | 18 | 25-75  | 53 | 74 | 92 | 12 | 30 | 36 | 2180 |
| 1630-2428250 | M24x28x250 | 27.7 | 44 | 18 | 70-120 | 53 | 74 | 92 | 12 | 30 | 36 | 2340 |
| 1630-3036200 | M30x36x200 | 35.6 | 54 | 22 | 25-75  | 68 | 88 | 94 | 14 | 30 | 46 | 3660 |
| 1630-3036250 | M30x36x250 | 35.6 | 54 | 22 | 70-120 | 68 | 88 | 94 | 14 | 30 | 46 | 3910 |

**Ürün Nr. 1630 Kombine "T" Ayaklı Saplama**

- Ağır preslerde, büyük kalıplarda çalışma esnasında vibrasyondan kaynaklanan olabilecek gevşemeyi somunun kontra sıkma yapısından dolayı önler
- Malzeme: 42 CrMo 4 DIN
- Kalite 12.9
- Siyah kaplama

**Product Nr. 1630 Combined "T" Slot Bolt**

- Because of it's contra tightening structure, it prevents loosening which may be generated by the vibration during working with heavy presses and big moulds.
- Material: 42 CrMo 4 DIN
- Quality 12.9
- Black coating



**Not:** 150 °C üzerindeki ortamlarda sıkma işlemi yapılırken dişlerin üzerine Loctite 8150 kullanılır.

**Note:** Environments on the 150 °C when clamping action on the thread Loctite 8150 is used.

