

Tek Dokunuş Dönmeli Üstten Bağlama

Swing Clamps With Cam Handle

Referans Nr.	Sıkma Yüksekliği Clamping Height				Sıkma Torku Clamping Stroke	İnme Torku Advance Stroke	L2	L3	L1	L4	W	L	H5	B
	Finiş Yüzey Temas Finished Surface Contact		Kaba Yüzey Temas Rough Surface Contact											
	Min.	Max.	Min.	Max.										
1481-0150R	31.3 (30.6-32)	33.3 (32.6-34)	32.2 (31.5-32.9)	34.2 (33.5-34.9)	1.4	1.1	30	8	35	15.3	45	23	8	5.3
1481-0200R	32.5 (31.7-33.2)	39 (38.2-39.7)	33.5 (32.7-34.2)	40 (39.2-40.7)	1.5	1.4	37	8	45	20.7	65	30	12	8.4
1481-0300R	36.5 (33.5-37.4)	46 (45-46.9)	39 (38-39.9)	48.5 (47.5-49.4)	1.9	1.7	45	8	55	25.4	85	40	15	10.5

Referans Nr.	Dp	H	D	W1	W2	H3	H2	M	H4	R	A	H1	İzin Verilen Çalışma Yüğü Allowable Operating Load (N)	Sıkma Kuvveti Clamping Force Kgf	 (g)
1481-0150R	34	66	23	10	5.3	14	40	M5	28.5	63	20	61.3	150	180	250
1481-0150L															
1481-0200R	48	82	30	16	8.4	18	50	M8	45.5	80	26	76.5	200	220	570
1481-0200L															
1481-0300R	64	100	40	20	10.4	22	60	M10	57	100	33	93	300	350	1200
1481-0300L															

**Ürün Nr. 1481 Tek Dokunuş Dönmeli Üstten Bağlama
Gövde**

- Malzeme: 42 CrMo 4 DIN
- Sertlik: 38-42 HRC
- Siyah Kaplama

Sıkma Mili


- Malzeme: Ck45 DIN
- Siyah Kaplama

Product Nr. 1481 Swing Clamps
Body

- Material: 42 CrMo 4 DIN
- Hardness: 38-42 HRC
- Black coated

Clamping Spindle

- Material: Ck45 DIN
- Black coated



Kullanım Şekli / How To Use

